

PRIME FILM

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
2 mil Clear Topcoated Elite Polypropylene	Biaxially oriented with a robust print receptive topcoating. Designed for use with water and solvent based flexo, UV flexo, UV letterpress and UV flatbed and rotary screen ink systems. Excellent clarity for “no label” look. Good for automatic and hand-applied label dispensing. Hot stamp compatible.	60"	28.8#	2	F UV
2 mil Metallized Topcoated Elite Polypropylene	Metallized, biaxially oriented polypropylene. Outstanding performance across a wide variety of printing processes including flexography, letterpress, offset, screen and gravure. It is highly compatible with UV, water-based, and solvent-based inks.	60"	31.3#	2	F UV
2.3 mil Gloss White Metallized Polypropylene	Biaxially oriented polypropylene film that is white on one side and has a metallized coating on the reverse side. The white side has a proprietary topcoat for superior printability across a wide variety of printing processes including flexo, offset, letterpress, screen and gravure. The metallized side provides superior opacity.	60"	38.9#	2.3	F
2 mil Holographic Polypropylene	Seamless metallized holographic with a rainbow appearance. Holographic films should be validated with the specific ink system before entering a full order.	40"	31.7#	2	F
2 mil Cracked Ice Holographic Polypropylene	Seamless metallized holographic with a cracked ice appearance. Holographic films should be validated with the specific ink system before entering a full order.	54"	31.7#	2	F
2.6 mil White Vision Gloss Topcoated Polypropylene	Biaxially oriented semi gloss film with proprietary topcoat for superior printability. Has a wide compatibility with a variety of thermal transfer ribbons.	54"	30#	2.6	F UV TT
3 mil White Vision Gloss Topcoated Polypropylene	Biaxially oriented semi gloss film with proprietary topcoat for superior printability. Has a wide compatibility with a variety of thermal transfer ribbons.	54"	36#	3	F UV TT
2.6 mil Gloss White Topcoated Elite Polypropylene	Super white, cavitated film. One side is coated with a special print receptive surface for excellent ink compatibility with a broad range of ink systems, including UV curing inks. The other side is coated for enhanced adhesive anchorage. Great dimensional stability with good heat resistance.	60"	30#	2.6	F UV
3.8 mil Matte White Polypropylene	Topcoated, biaxially oriented. Suitable for use with wax/resin ribbons.	60"	49.5#	3.7	F UV TT
2 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54"	32.9#	2	F
2.5 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54"	41#	2.5	F
2 mil Clear Topcoated Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54"	40#	2	F UV TT
2 mil White Topcoated Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54"	42#	2	F UV TT
2 mil Bright Silver Topcoated Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54"	43.5#	2	F UV TT
2 mil Matte Silver Topcoated Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54"	42#	2	F UV TT
3.2 mil Clear Matte Non-Topcoated Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	74#	3.2	F
3.5 mil White Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	74#	3.5	F
3.5 mil White Topcoated Vinyl	Tough, durable polymeric plastic film. Excellent resistance to oils, chemicals and some solvents. Contains a proprietary topcoating that is compatible with solvent and water-based inks. Abrasion resistant. Good choice for outdoor labeling.	54"	74#	3.5	F
3.2 mil Black Non-Topcoated Vinyl	Cadmium free vinyl formulated for use in the label / decal sign market. It has excellent surface quality, printability and product consistency.	54"		3.2	F
3.5 mil Yellow Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"		3.5	F
5 mil White Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"		5	F
6 mil White Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"		6	F

VARIABLE PRINT FILM

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
2 mil Clear Direct Thermal	A direct thermal BOPP that offers high thermal sensitivity and clean image formation. Also offers good water and oil resistance and good dimensional stability.	39"		2	DT
1.6 mil White Direct Thermal	High durability and sensitivity. Ideal for bar code or demand printed retail, commercial or industrial marking. Excellent flexographic printability with wet rub resistance and thermal image durability against water, alcohol, oils and plasticizers.	29.7"		1.6	F DT
3 mil White Direct Thermal Polypropylene	High durability and sensitivity. Ideal for bar code or demand printed retail, commercial or industrial marking. Excellent flexographic printability with wet rub resistance and thermal image durability against water, alcohol, oils and plasticizers.	60"	37.7#	3.1	F DT
2 mil White Polyester CITC	Proprietary computer imprintable matte topcoating that accepts laser, dot matrix and thermal transfer printing, as well as, conventional silk screen, flexographic and offset/ letterpress inks.	54"	42#	2	F UV L TT
46# C1S Syntharm®	Topcoated, high-density, conformable polyethylene. Designed for thermal transfer applications that require more durability than paper or tag stock. Accepts wax, wax/resin and resin ribbons.	60"	46#	3.6	F TT
2.6 mil Matte White Premium Thermal Transfer Polypropylene	A white cavitated film with excellent anchorage for a wide range of adhesives. Good high-speed press performance, outstanding opacity and whiteness, good dimensional stability, heat resistance and die-cutting performance.	54"	30#	2.6	F TT
3 mil Matte Premium Thermal Transfer Polypropylene	Cavitated film with excellent anchorage for a wide range of adhesives. Good high-speed press performance, outstanding opacity and whiteness, good dimensional stability, heat resistance and die-cutting performance.	54"	36#	3	F TT
3.2 mil White Thermal Transfer Endure	Matte, thermal transfer printable and conformable polyolefin. Excellent candidate for applications that require durability and strength. Good resistance to moisture, chemicals and UV. Compatible with a wide variety of print systems.	54"	56.5#	3.2	F UV TT
3.8 mil Matte White Polypropylene	Topcoated, biaxially oriented. Suitable for use with wax/resin ribbons.	60"	49.5#	3.7	F TT
3.5 mil White HT Topcoated Vinyl	A tough, durable, polymeric vinyl exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labels. Formulated to withstand higher temperatures without softening. Contains a proprietary topcoating that is compatible with solvent and water-based inks.	54"	74#	3.5	F L
4 mil Thermal Transfer Valéron®	Super strong, oriented and cross-laminated thermal transfer film with outstanding elongation and barrier characteristics. Flexo print receptive. Use wax or wax/resin ribbons for best results.	54"	55.8#	4	F TT
Kimdura® Inkjet Ultra* BS5609 SECTION 2 CERTIFIED	Matte white in appearance. Designed for applications where exceptional durability, outdoor weatherability and chemical resistance are required. Ideal for drum/chemical/ industrial labeling, workplace hazard communications, logistics and healthcare labeling.	60"		5	P
Kimdura® Topcoated	Moisture resistant, biaxially oriented polypropylene. Compatible with a wide variety of thermal transfer ribbons.	52"	62#	4.2	F TT
0.5 mil, 1 mil and 2 mil Clear Laser Topcoated Polyester	Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing. Ideal for use with flexo, screen, letterpress and offset printing methods.	60"			F L UV TT
5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing.	54"		5.5	F L UV TT
7.5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing.	54"		7.5	F L UV TT
7 mil White Teslin®	Uncoated, porous, highly filled polyolefin that is printable, durable, waterproof, secure and adaptable. It bonds readily and firmly with toners inks, adhesives, coatings and laminating films.	54"	77#	7	F UV TT HP P L
6 mil Polyolith®	White, opaque, two side matte finish. Excellent candidate for a wide range of applications where durability, strength, moisture, chemical resistance and superior printability are required. An excellent label and card stock. Outstanding combination of strength and rigidity.	51.5"	116#	6	F TT
10 mil Polyolith® * custom order	Two side, matte finish, white, opaque film. Excellent candidate for a wide range of applications where durability, strength, moisture, chemical resistance and superior printability are required. An excellent label and card stock, it has an outstanding combination of strength and rigidity.	51.5"	194#	10	F TT

* BS5609 Section 3 Certified by EPSON C3500, C3400, C831, C7500 using EPSON DURABright® Ultra (Cyan, Magenta, Yellow, Black).

OVERLAMINATES

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
0.5 mil Clear Non-topcoated Polyester	Optically clear. Excellent for use in applications requiring a durable overlaminate.	60"		.48	
1 mil Clear Non-topcoated Polyester	Optically clear. Smooth surface, high gloss and good dimensional stability. Excellent for use in applications requiring a durable overlaminate.	54"		1	
1 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film.	60"		1	F L
1 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		1	F L
2 mil Clear Non-topcoated Polyester	Strong. Good resistance to moisture, solvents, oils and high temperatures. Chemically primed for ink receptivity. Dimensionally stable, high strength and excellent chemical resistance.	60"		2	
2 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film with high resistance to scratching and abrasions.	60"		2	F L
2 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		2	F L

SPECIALTY FILM

3.5 mil White Dry Erase Vinyl	Topcoated white film designed for use with dry erase markers.	54"		3.5	
Tyvek® 1073D	Spun-bonded polyolefin with very high internal strength and exceptional tear resistance.	54"	45.8#	7.5	F
5 mil Black Chalkboard Vinyl	Unique matte black vinyl designed to accept standard chalk. Good for use in classrooms, dorm rooms, home and office.	54"		5	F

PRIME PAPER

35# C1S Litho **	Premium quality, mid gloss. Excellent conformability to small radius substrates. Most often used for pharmaceutical applications. Excellent strength to weight ratio. Crack resistant coating.	60"	35#	2.5	F UV
60# Semi Gloss **	Super bright, two-side printable. Excellent solution for use across multiple printing platforms. Ideal for instant redeemable coupon applications.	60"	60#	2.8	F UV
60# Matte Litho **	A premium quality C1S matte litho providing excellent printing and processing characteristics. Ion deposition printable.	60"	60#	3.2	F UV TT
54# Wet Strength High Gloss **	A gloss coated wet strength paper with resistances to an alkaline solution. Suitable for sheet-fed and offset rotogravure printing method.	54"	54#	2.5	F
53# Latex Paper	Abrasion/scratch resistant, smudge-free, hand writeable, and resists chemicals/solvents.	60"	53#	3.6	F L
57# High Gloss ■	High bright, cast coated. High internal strength, excellent ink receptivity and converting properties.	60"	57#	3.7	F UV
50# Uncoated Litho ■	High quality, smudge resistant. High-speed converting properties. Highly receptive to inks and markings of commonly used data systems.	60"	50#	3.5	F UV
50# Brown Kraft ■	A natural Kraft paper.	54"	53#	3.2	F
60# Hemp Paper	A woven vellum finished paper, made of 25% hemp and 75% post consumer wood.	60"	60#	5.5	F

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

acucote.com

VARIABLE PRINT PAPER

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
Universal Thermal Transfer *	Matte coated grade for use in thermal transfer printing. Excellent flexographic printing properties, no mottle, high brightness, and improved coating for extended die life. Wax-based ribbons are recommended with proper testing.	60"	38#	2.8	F TT
Direct Thermal HS	A bright white grade formulated for sharp imaging on a wide variety of direct thermal printers. Topcoated for resistance to blood, oil, fats and moisture. Good light stability for resistance to fading and background discoloration from UV light exposure. Suitable for flexographic pre-printing.	60"	46.5#	3.1	F UV DT
50# EDP **	High quality and smudge-resistant. High-speed converting properties. Extremely receptive to inks and markings of commonly used data systems.	60"	50#	3.5	F L
Economy Laser *	Conformable, low-memory face. Good image contrast with low substrate show through. Suitable for a wide range of laser print systems.	60"	50#	3.5	F L
VIP Premium *	A super smooth, high-bright laser and inkjet compatible stock.	54"	50#	3.8	F L

BOARDSTOCK

8pt C1S High Bright *	Blue-white boardstock. Superior printability and appearance for a wide variety of print systems.	60"	108#	8	F UV
8pt Recycled C1S * ⁿ	10% post consumer waste recycled content.	60"	103#	8	F UV
8pt Uncoated * ⁿ	Good printability and appearance for a wide variety of print systems.	60"	103#	8	F UV
10pt C1S * ⁿ	Superior printability and appearance for a wide variety of print systems.	52"	118#	10	F UV
12pt C1S * ⁿ	Superior printability and appearance for a wide variety of print systems.	52"	133#	12	F UV
12pt Uncoated * ⁿ	Good printability and appearance for a wide variety of print systems.	52"	133#	12	F UV

FLUORESCENT

60# Red **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Orange **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Chartreuse **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Green **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	54"	59#	4.3	F
60# Pink **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	54"	59#	4.3	F

FOILS & METALLIZED PAPER

Bright Silver *	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Dull Silver *	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Bright Gold *	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Dull Gold *	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Silver Metallized Paper	Highly reflective. Offers conformability, strength and ink receptivity.	60"	51#	2.7	F UV

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

6
ACUCOTE MANTER

acucote.com

SPECIALTY PAPER

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
2 mil Clear Acetate	Cellulose based. Exhibits rigidity, dimensional stability and good ink receptivity. Excellent converting properties. Not recommended for outdoor use.	52"		2	F
54# Wet Strength High Gloss	Designed for applications where moisture or condensation is typically present. Excellent print surface and good converting properties.	60"	54#	2.5	F
Black Imaging Paper	Carbonless, self-contained pressure, black imaging facestock. Extremely sensitive. Can be silicone coated for use in multiply constructions or as a liner.	60"	22.5#	3.9	F

MAIL TABS

2 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54"	32.9#	2	F
2.5 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54"	41#	2.5	F
Translucent MC Ultra *	Exceptionally clear, translucent paper for mail tab applications where the highest level of view-through to the printed piece is required. Excellent converting and winding characteristics. An alternative to clear polystyrene mail tabs.	60"	43#	2.1	F
Translucent MC	Moderate translucent paper. Should be considered for mail tab applications where modest view-through to the printed piece is required. Excellent converting and winding characteristics.	60"	40#	2.7	F
RC Mail Tab	Reverse coated paper used for mail tab closures.	60"	40#	2.6	F

DIAMOND-COTE® EZ COUPON (TWO-SIDED MESSAGE)

Diamond-Cote® EZ	Designed to be laminated with 50# to 60# basis weight facestocks to create one or two-side printed instant redeemable coupons. Universal release from any edge.	60"		1.5	F UV
------------------	---	-----	--	-----	------

DIAMOND-COTE SP® COUPON (SINGLE-SIDED MESSAGE)

60# Semi Gloss Diamond-Cote® SP	60# semi gloss uniquely laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	60"	94#	4	F UV
Red Fluorescent Diamond-Cote® SP	60# red fluorescent uniquely laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	60"	153#	4	F
Thermal Transfer Diamond-Cote® SP	Thermal transfer uniquely laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	60"	136#	8	F TT
Direct Thermal HS Diamond-Cote® SP	Bright white direct thermal uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	137#	8.6	F UV DT
2.6 Mil Elite Polypropylene Diamond-Cote® SP	Super white cavitated film laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	60"	123#	8	F UV TT

IRCOMPLETE® COUPON (SINGLE-SIDED & TWO-SIDED MESSAGE)

IRComplete®	A single-ply, instant redeemable coupon utilizing a 2 mil clear topcoated polypropylene laminated to a thin, clear polypropylene. This solution permits single or double side printing.	60"		2.5	F
UV IRComplete®	A single-ply, instant redeemable coupon utilizing a 2 mil clear topcoated polypropylene laminated to a thin, clear polypropylene. This solution permits single or double side printing.	60"		2.5	F UV
HP IRComplete®	A single-ply, instant redeemable coupon utilizing a 2 mil clear topcoated polypropylene laminated to a thin, clear polypropylene. This solution permits single or double side printing.	60"		2.5	F HP

DIAMOND-COTE® RELEASE TAG

8pt Dry Tag	NPS tag utilizing a 3.2 base and dry adhesive technology for single-side messaging. Tag is peeled from the base carrier without leaving adhesive on the facestock or the liner.	60"	205#	14	F L
10pt Dry Tag	NPS tag utilizing a 3.2 base and dry adhesive technology for single-side messaging. Tag is peeled from the base carrier without leaving adhesive on the facestock or the liner.	52"	222#	16	F L
12pt Dry Tag	NPS tag utilizing a 3.2 base and dry adhesive technology for single-side messaging. Tag is peeled from the base carrier without leaving adhesive on the facestock or the liner.	52"	238#	18	F L

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

acucote.com

7

AFFIXED CARDS: LIFTCOTE® AND DIAMOND-COTE® TIGHT (TWO-SIDED MESSAGE)

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
Diamond-Cote® Tight	Designed to be laminated with heavy-weight facestocks to create two-side printed temporary ID cards. The universal pattern allows any die cut shape to be lifted and released cleanly without residue. Coming soon - product improvements underway	60"		1.5	F UV
2-Up LiftCote® 7.5"	Designed to be laminated with heavy-weight facestocks to create temporary ID cards.	60"		1.5	F UV
3-Up LiftCote® 11.25"	Designed to be laminated with heavy-weight facestocks to create temporary ID cards.	60"		1.5	F UV
4-Up Lift Cote® 15"	Designed to be laminated with heavy-weight facestocks to create temporary ID cards.	60"		1.5	F UV
LiftCote® Longfeed	Designed to be manufactured in "portrait" orientation and to be laminated with heavy-weight facestocks to create temporary ID or retail buyers cards.	60"		1.5	F UV

* LiftCote® products have a narrow, ungummed patterned edge that allows for easy lifting and removal. They are designed for high-speed automatic applications. Flexographic inks reverse coated on the film layer produce two-side printed cards.

COUPON COMPANION PRODUCTS

5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Provides superior toner and ink adhesion for laser and thermal transfer printing. Ideal for use with flexo, screen, letterpress, and offset printing methods.	54"		5	F UV L
7.5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing. Ideal for use with flexo, screen, letterpress, and offset printing methods.	54"		7.5	F UV L
8pt Board	NPS tag utilizing a 3.2 base and dry adhesive technology for single-side messaging. Tag is peeled from the base carrier without leaving adhesive on the facestock or the liner.	60"	108#	8	F UV L

INTEGRATED CARDS

Universal LiftCote®	Designed for integrated forms card applications that do not require lift lanes. The peeled layer has a 2 mil clear reinforcement film for the card and a 1.5 mil clear film base left on the form.	60"		3.5	F UV
LiftCote® Plus Wide	Designed for integrated forms card applications, then narrow ungummed patterned edge allows for easy lifting and removal. The peeled layer has a 2 mil clear reinforcement film for the card and a 1.5 mil clear film base left on the form.	60"		3.5	F UV

TAMPER EVIDENT

55# TE Litho *	Uncoated, white, highly destructible paper.	54"	55#	3.1	F
2 mil Silver Void Polyester	Selective release film with an imprinted silver "void" pattern to show undeniable evidence of tampering. Versatile topcoat suitable for solvent and water-based flexo, solvent based gravure as well as screen inks and selected UV inks. Topcoat is thermal transfer compatible.	54"		2	F UV TT
2 mil White Void Polyester	Selective release film with an imprinted white "void" pattern to show undeniable evidence of tampering. Versatile topcoat suitable for solvent and water-based flexo, solvent based gravure as well as screen inks and selected UV inks. Topcoat is thermal transfer compatible.	54"		2	F UV TT
Syntherm® TE	Topcoated, high-density polyethylene designed to destruct when removed. Accepts wax, wax/resin and resin thermal transfer ribbons.	60"	41#	4.1	F TT
2 mil Clear Acetate UD	Clear film with a gloss topcoat for enhanced printability. Film tears easily showing evidence of tampering. High level of destructibility with exceptional die cutting characteristics.	51.5"	44#	2	F
Diamond-Cote® Safety Peel	Using Diamond-Cote® EZ coupon technology, Acucote prints a customized message/ logo between the leave behind ply and the pressure-sensitive adhesive that bonds the closure/coupon to the package. The result is an opportunity to convey a security message, or, to promote additional brand identity on the leave behind film that remains on the food packaging once the closure/coupon is removed. Retailers are then printing promotional messages on this tamper-evident closure/coupon.	60"		1.5	F UV

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

8
ACUCOTE MANTER

acucote.com

SUSTAINABLE

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
40# Water Soluable Litho	Printable and writable water-soluble paper that will dissolve in water and wash away easily.	45"	40#	3	F
47# Water Dissolvable Direct Thermal	A water dissolvable and writable facestock. All material should be wrapped in plastic and suspended to increase longevity. 60 day shelf life. Avoid direct sun light and elevated temperature and humidity.	45"	47#	4	DT
50# Uncoated Litho ■	High quality, smudge resistant. High-speed converting properties. Highly receptive to inks and markings of commonly used data systems.	60"	50#	3.5	F
60# Hemp Paper	A woven vellum finished paper, made of 25% hemp and 75% post consumer wood.	60"	60#	5.5	F
8pt C1S Recycled **	Smooth with 10% post consumer waste recycled content.	60"	103#	8	F
8pt Uncoated Recycled **	Smooth with 10% post consumer waste recycled content. Good printability and appearance for a wide variety of print systems.	60"	103#	8	F
2 mil Clear Acetate	Matte cellulose based. Exhibits rigidity, dimensional stability and good ink receptivity. Excellent converting properties. Not recommended for outdoor use.	52"		2	F
2 mil Clear Acetate UD	Film tears easily showing evidence of tampering. High level of destructibility with exceptional die cutting characteristics.	51.5"	44#	2	F
2 mil Clear EarthFirst®	Compostable. Made from an annually renewable resource. Excellent slip characteristics, high natural dyne level and excellent scratch resistance.	54"	41#	2	F

FSC® CERTIFIED - MUST SPECIFY FSC® CERTIFIED WHEN ORDERING MATERIALS

35# C1S Litho **	Premium quality, mid gloss. Excellent conformability to small radius substrates. Most often used for pharmaceutical applications. Excellent strength to weight ratio. Crack resistant coating.	60"	35#	2.5	F UV
60# Semi Gloss **	Versatile, consistent and two-side printable. Suitable for roll label and sheet-fed applications. Excellent solution for use across multiple printing platforms. Ideal for instant redeemable coupon applications.	60"	60#	2.8	F UV
60# Matte Litho **	A premium quality C1S matte litho providing excellent printing and processing characteristics. Ion deposition printable.	60"	60#	3.2	F UV TT
55# TE Litho	Uncoated, white, highly destructible paper.	54"	55#	3.1	F
54# Wet Strength High Gloss	A gloss coated wet strength paper with resistances to an alkaline solution. Suitable for sheet-fed and offset rotogravure printing method.	54"	54#	2.5	F
Universal Thermal Transfer	Matte coated grade for use in thermal transfer printing. Excellent flexographic printing properties, no mottle, high brightness, and improved coating for extended die life. Wax-based ribbons are recommended with proper testing.	60"	38#	2.8	F TT
50# EDP ■	High quality and smudge-resistant. High-speed converting properties. Extremely receptive to inks and markings of commonly used data systems.	60"	50#	3.5	F L
Economy Laser	Conformable, low-memory face. Good image contrast with low substrate show through. Suitable for a wide range of laser print systems.	60"	50#	3.5	F L
VIP Premium	A super smooth, high-bright laser and inkjet compatible stock.	54"	50#	3.8	F L
8pt C1S High Bright	Blue-white boardstock. Superior printability and appearance for a wide variety of print systems.	60"	108#	8	F UV
8pt Recycled C1S ■	10% post consumer waste recycled content.	60"	103#	8	F UV
8pt Uncoated ■	Good printability and appearance for a wide variety of print systems.	60"	103#	8	F UV
10pt C1S ■	Superior printability and appearance for a wide variety of print systems.	52"	118#	10	F UV
12pt C1S ■	Superior printability and appearance for a wide variety of print systems.	52"	133#	12	F UV
12pt Uncoated ■	Good printability and appearance for a wide variety of print systems.	52"	133#	12	F UV
14pt C1S ■	Superior printability and appearance for a wide variety of print systems.	52"	160#	14	F UV
60# Red Fluorescent **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Orange Fluorescent **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F

cont.

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

acucote.com

9

FSC® CERTIFIED CONT - MUST SPECIFY FSC® CERTIFIED WHEN ORDERING MATERIALS

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
60# Chartreuse Fluorescent **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Green Fluorescent **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Pink Fluorescent **	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
Bright Silver Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Dull Silver Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Bright Gold Foil	Good printability and appearance for a wide variety of print systems.	60"	70#	3.6	F UV
Dull Gold Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
60# Waterjet® High Gloss	Bright white in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	64#	4	D P F
60# Extra Bright Waterjet® Semi Gloss	Bright white in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	60#	4.3	D P F
60# Waterjet® Premium Matte	Bright in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	64#	5	D P F

HEAT SEAL

Heat Seal Coatings	Coatings are available for a wide range of food, medical and industrial packaging applications. Activation temperature +200 - +225F. Available for film and paper facestocks. Contact your sales representative to learn more.
--------------------	--

INKJET - UV

2 mil Clear UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	60"	40#	2	UVI F
2 mil White UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	54"	42#	2	UVI F
2 mil Bright Silver UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	54"	43.5#	2	UVI F
2 mil Matte Silver UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	54"	42#	2	UVI F
2 mil Clear UV GL Polypropylene	Biaxially oriented with a glossy topcoating for improved quality for latex, UV and solvent digital inks. Backside coated for excellent adhesive anchorage.	60"	31.6#	2	UVI F
2 mil Metallized UV GL Polypropylene	Biaxially oriented with a glossy topcoating for improved quality for latex, UV and digital inks. Backside coated for excellent adhesive anchorage.	60"	41#	2	UVI F
2.6 mil White UV GL Polypropylene	High opacity, biaxially oriented with high gloss and good stiffness for automatic label dispensing. Backside coated for excellent adhesive anchorage.	60"	30.2#	2.7	UVI F
3.5 mil White UV GL Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	81.6#	3.5	UVI F
60# UV Semi Gloss ■	Super bright-white appearance.	60"	60#	2.8	UVI F
57# UV High Gloss ■	Bright cast coated paper. High internal strength and converting properties.	60"	57.4#	3.7	UVI F
Silver Metallized UV GL Paper	Highly reflective silver metallized paper offering conformability, strength and ink receptivity.	60"	56#	2.6	UVI F
8pt C1S UV GL Board ■	10% post consumer waste recycled content.	60"	103#	8	UVI F
Bright Silver UV GL Foil	Acrylic, foil that are laminated to a bleached kraft base sheet.	60"	70#	3.6	UVI F
60# UV Semi Gloss Diamond-Cote SP®	A 60# Semi Gloss sheet uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	94#	4.9	UVI F
Silver UV GL Polyester Void	Selective release film with an imprinted silver "void" pattern to show undeniable evidence of tampering.	54"		2	UVI F
UV IRComplete®	A single-ply, instant redeemable coupon utilizing a 2 mil clear topcoated polypropylene laminated to a thin, clear polypropylene. This solution permits single or double side printing.	60"		2.5	UVI F

Products are topcoated to enhance the print quality on UV Inkjet presses. Media should be validated by the specific print system.

cont.

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

acucote.com

INKJET - DYE AND PIGMENT

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
2 mil Gloss Clear Waterjet® Polyester	A clear gloss film. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	41.2#	2	D P F
3.5 mil Gloss White Waterjet® Polypropylene	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	43.5#	3.5	D P F
3.5 mil Matte White Waterjet® Polypropylene	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	39#	3.5	D P F
4 mil Metallized Waterjet® Polyester -Polypropylene	A blend of polyester and biaxially oriented metallized polypropylene film with a topcoating for water based inkjet printability.	60"	41	4	D P F
60# Waterjet® High Gloss *	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	64#	4	D P F
60# Extra Bright Waterjet® Semi Gloss *	Bright white in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	60#	4.3	D P F
60# Waterjet® Premium Matte *	Bright in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	64#	5	D P F
60# Extra Bright Waterjet® Diamond-Cote SP®	A 60# Semi Gloss sheet uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	98#	6.4	D P F
Endura® Inkjet Durable Paper	Matte white latex saturated paper with outstanding durability and conformability. This stock is abrasion/scratch resistant, smudge-free, handwriteable and resists chemicals/solvents. Ideal for: drum/chemical/industrial labeling, workplace hazard communications, logistics labeling, healthcare labeling, coupons/shelf marketing.	60"		5	D P

Waterjet® media should be validated by the specific print system.

INKJET - PIGMENT

Kimdura® Inkjet Ultra* BS5609 SECTION 2 CERTIFIED	Matte white in appearance. Designed for applications where exceptional durability, outdoor weatherability and chemical resistance are required. Ideal for drum/chemical/ industrial labeling, workplace hazard communications, logistics and healthcare labeling.	60"		5	P
---	---	-----	--	---	---

* BS5609 Section 3 Certified by EPSON C3500, C3400, C831, C7500 using EPSON DURABright® Ultra (Cyan, Magenta, Yellow, Black). Media should be validated by the specific print system.

LASER

3.5 mil White Laser Topcoated Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	52#	3.5	F L
2 mil Clear Toner** Polypropylene	Clear biaxially oriented film. Excellent clarity for "no label" look. Good for automatic and hand applied label dispensing. Hot stamp compatible.	60"	28.8#	2	F L
2 mil Metallized Toner** Polypropylene	Biaxially oriented polypropylene with a glossy topcoating for improved quality for latex, UV and digital inks. Backside coated for excellent adhesive anchorage.	60"	31.3#	2	F L
2.6 mil White Toner** Polypropylene	High opacity, biaxially oriented film. Good stiffness for automatic label dispensing. Backside coated for excellent adhesive anchorage.	60"	30#	2.6	F L
2 mil White Polyester CITC	Proprietary computer imprintable matte topcoated film.	54"	42#	2	F UV TT
5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage.	54"		5.5	F L UV TT
7.5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage.	54"		7.5	F L UV TT
7 mil White Teslin® BS5609 SECTION 2 CERTIFIED	Uncoated, porous, highly filled polyolefin that is printable, durable, waterproof, secure and adaptable. It bonds readily and firmly with toners inks, adhesives, coatings and laminating films. BS5609 Sect. 2 certified on Laser systems.	54"	77#	7	F UV TT HP L P
53# Latex Paper	Abrasion/scratch resistant, smudge-free, hand writeable, and resists chemicals/solvents.	60"	53#	3.6	F L
Economy Laser *	Conformable, low-memory face. Good image contrast with low substrate show through. Suitable for a wide range of laser print systems.	60"	50#	3.5	F L
VIP Premium *	A super smooth, high-bright white laser and inkjet compatible stock.	54"	50#	3.8	F L
60# Laser Semi Gloss ■	Versatile, laser printable stock.	60"	60#	2.8	F L

Products are topcoated to enhance the print quality on laser presses. ** Dependent on heat generated, testing is required.

cont.

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

acucote.com

11

LASER CONT

Product		Width	Basis Wt.	Cal/ Mil	Print Tech.
57# Laser High Gloss ■	Bright, versatile, laser printable stock.	60"	57.4#	3.7	F L
1 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film.	60"		1	F L
1 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		1	F L
2 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film with high resistance to scratching and abrasions.	60"		2	F L
2 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		2	F L
Bright Silver Laser Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F L
Bright Gold Laser Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F L

Products are topcoated to enhance the print quality on laser presses. ** Dependent on heat generated, testing is required.

HP INDIGO

2 mil Clear HP TC Polypropylene	Clear biaxially oriented film. Excellent clarity for "no label" look. Good for automatic and hand applied label dispensing. Hot stamp compatible.	60"	31.6#	2	HP F
2 mil Metallized HP TC Polypropylene	Biaxially oriented polypropylene with a glossy topcoating for improved quality for latex, UV and digital inks. Backside coated for excellent adhesive anchorage.	60"	41#	2	HP F
2.6 mil Gloss White HP TC Polypropylene	High opacity, biaxially oriented film. Good stiffness for automatic label dispensing. Backside coated for excellent adhesive anchorage.	60"	30.2#	2.7	HP F
3.5 mil White HP TC Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	52#	3.5	HP F
60# HP TC Semi Gloss ■	Super bright-white appearance suitable for roll-label and sheet-fed applications.	52"	60#	2.8	HP F
57# HP TC High Gloss ■	Bright cast coated gloss paper. High internal strength and converting properties.	52"	57.4#	3.7	HP F
Bright Silver HP Metallized Paper	Highly reflective. Offers conformability, strength and ink receptivity.	60"	51#	2.7	HP F
Bright Silver HP Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	HP F
Bright Gold HP Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	HP F
60# HP Semi Gloss Diamond-Cote® SP	A 60# Semi Gloss sheet uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	94#	4.9	HP F
HP IRComplete®	A single-ply, instant redeemable coupon utilizing a 2 mil clear topcoated polypropylene laminated to a thin, clear polypropylene. This solution permits single or double side printing.	60"		2.5	HP F

Products are topcoated to enhance the print quality on HP presses.

Terms & Conditions:

Pre-testing is recommended using the printer(s) and ink system(s) to ensure compatibility. EarthFirst®, Kimdura®, Opticite®, Polyolith®, Syntherm®, Tyveck® and Valéron® are trademarks of the respected suppliers. Freight costs are set at a flat per msi rate. Acucote reserves the right to change, modify, or delete any product or program listing without notification.

F - Flexo, UV - UV Flexo, TT - Thermal Transfer, DT - Direct Thermal, L - Laser, HP - HP, UVI - UV Inkjet, D - Dye, P - Pigment

* FSC Certified available - must specify FSC Certified when ordering materials ■ USDA Certified Biobased Product

800.228.2683 Graham, NC

acucote.com