

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/MIL	PRINT TECH.
PRIME FILM					
2 mil Clear Topcoated Polypropylene	Biaxially oriented with a robust print receptive topcoating. Designed for use with water and solvent based flexo, UV flexo, UV letterpress and UV flatbed and rotary screen ink systems. Excellent clarity for “no label” look. Good for automatic and hand-applied label dispensing. Hot stamp compatible.	60”	28.8#	2	F UV
2 mil High Gloss Clear Topcoated Flex	Clear, high gloss, surface printable polyolefin film with enhanced conformability and squeezability. Offers improved flexibility for use on containers where conformable and squeezable properties are required.	54”	28.6#	2	F UV
2 mil Metallized Topcoated Elite Polypropylene	Metallized, biaxially oriented polypropylene. Outstanding performance across a wide variety of printing processes including flexography, letterpress, offset, screen and gravure. It is highly compatible with UV, water-based, and solvent-based inks.	54”	31.3#	2	F UV
2.6 mil White Vision Gloss Topcoated Polypropylene	Biaxially oriented topcoated for superior printability. Has a wide compatibility with a variety of thermal transfer ribbons.	54”	30#	2.6	F UV TT
2.4 mil Gloss White Topcoated Polypropylene	Biaxially oriented with a proprietary topcoating for superior printability. Designed for use in demanding PSAs where superior ink adhesion is important. High gloss with excellent UV, aqueous and solvent ink compatibility. Backside coated for excellent adhesive anchorage.	60”	28#	2.4	F UV
2.6 mil Gloss White Topcoated Elite Polypropylene	High opacity, biaxially oriented with a proprietary topcoating for superior printability. Designed for use in demanding PSAs where superior ink adhesion and opacity are important. High gloss and good stiffness for automatic label dispensing. Excellent compatibility with UV, aqueous and solvent inks. Backside coated for excellent adhesive anchorage.	60”	30.2#	2.6	F UV
3.8 mil Matte White Polypropylene	Topcoated, biaxially oriented. Suitable for use with wax/resin ribbons.	60”	49.5#	3.7	F UV TT
2 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54”	32.9#	2	F
2.5 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54”	41#	2.5	F
2 mil Clear Topcoated Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54”	40#	2	F UV TT
2 mil White Topcoated Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54”	42#	2	F UV TT
2 mil Bright Silver Topcoated Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54”	43.5#	2	F UV TT
2 mil Matte Silver Polyester	Printable topcoating suitable for solvent and water-based UV, offset letterpress inks. Designed to accept a wide variety of thermal transfer ribbons.	54”	42#	2	F UV TT
3 mil Clear Gloss Non-Topcoated Vinyl	Ultra clear polymeric vinyl exhibiting excellent resistance to oils, chemicals, and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54”		3	F UV
3.2 mil Clear Matte Non-Topcoated Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54”	74#	3.2	F
3.5 mil White Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54”	74#	3.5	F
3.5 mil White Topcoated Vinyl	Tough, durable polymeric plastic film. Excellent resistance to oils, chemicals and some solvents. Contains a proprietary topcoating that is compatible with solvent and water-based inks. Abrasion resistant. Good choice for outdoor labeling.	54”	74#	3.5	F L
3.5 mil Red Non-Topcoated Vinyl	Cadmium free vinyl formulated for use in the label / decal sign market. It has excellent surface quality, printability and product consistency.	54”		3.5	F
3.5 mil Black Non-Topcoated Vinyl	Cadmium free vinyl formulated for use in the label / decal sign market. It has excellent surface quality, printability and product consistency.	54”		3.5	F
3.5 mil Yellow Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54”		3.5	F

cont.

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/MIL	PRINT TECH.
PRIME FILM CONT.					
5 mil White Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"		5	F
6 mil White Non-Topcoated Vinyl	Tough, durable polymeric plastic film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"		6	F
VARIABLE PRINT FILM					
3 mil Platinum Thermal™ Mobile Printer	Polyolefin film with a single-layer polymer replacing both direct thermal and the use of thermal transfer ribbons. Recommended for mobile printers. Sharp, durable and fade-proof images. Heat stable up to 130°C with UV light-resistant image with estimated outdoor life of 18 months. Testing required.	54"	30.2#	3	F DT TT
2 mil Clear Direct Thermal	A direct thermal BOPP that offers high thermal sensitivity and clean image formation. Also offers good water and oil resistance and good dimensional stability.	39"		2	DT
1.6 mil White Direct Thermal	High durability and sensitivity. Ideal for bar code or demand printed retail, commercial or industrial marking. Excellent flexographic printability with wet rub resistance and thermal image durability against water, alcohol, oils and plasticizers.	29.7"		1.6	F DT
3 mil White Direct Thermal Polypropylene	High durability and sensitivity. Ideal for bar code or demand printed retail, commercial or industrial marking. Excellent flexographic printability with wet rub resistance and thermal image durability against water, alcohol, oils and plasticizers.	60"	37.7#	3.1	F DT
4.1 mil White Direct Thermal Polypropylene	Durable with high sensitivity and high density. Ideal for use in high-speed direct thermal printers. Offers excellent thermal side flexographic printability and wet rub resistance. Thermal image durability against water, alcohol, oil and plasticizers.	60"	51#	4.1	F DT
2 mil White Polyester CITC	Proprietary computer imprintable matte topcoating that accepts laser, dot matrix and thermal transfer printing, as well as, conventional silk screen, flexographic and offset/letterpress inks.	54"	42#	2	F UV L
46# C1S Syntherm®	Topcoated, high-density, conformable polyethylene. Designed for thermal transfer applications that require more durability than paper or tag stock. Accepts wax, wax/resin and resin ribbons.	60"	46#	3.6	F TT
2.6 mil Matte White Premium Thermal Transfer Polypropylene	Wide compatibility with thermal transfer ribbons. Excellent print resolution and abrasion resistance.	54"	30#	2.6	F TT
3 mil Matte White Thermal Transfer Polypropylene	White, opaque, biaxially oriented film. Designed for demanding thermal transfer applications. Compatible with a wide range of solvent or water-based flexo, gravure and screen UV ink systems. Backside coated for excellent adhesive anchorage.	54"	33#	3	F UV TT
3.2 mil White Thermal Transfer Endure	Matte, thermal transfer printable and conformable polyolefin. Excellent candidate for applications that require durability and strength. Good resistance to moisture, chemicals and UV. Compatible with a wide variety of print systems.	54"	56.5#	3.2	F UV TT
3.8 mil Matte White Polypropylene	Topcoated, biaxially oriented. Suitable for use with wax/resin ribbons.	60"	49.5#	3.7	F TT
3.5 mil White HT Topcoated Vinyl	A tough, durable, polymeric vinyl exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labels. Formulated to withstand higher temperatures without softening. Contains a proprietary topcoating that is compatible with solvent and water-based inks.	54"	74#	3.5	F L
4 mil Thermal Transfer Valéron®	Super strong, oriented and cross-laminated thermal transfer film with outstanding elongation and barrier characteristics. Flexo print receptive. Use wax or wax/resin ribbons for best results.	54"	55.8#	4	F TT
DualTech® Kimdura®	Matte white in appearance. Designed for applications where exceptional durability, outdoor weatherability and chemical resistance are required. Ideal for drum/chemical/industrial labeling, workplace hazard communications, logistics and healthcare labeling.	60"		3.5	L I/P
Inkjet Kimdura® Ultra*	Matte white in appearance. Designed for applications where exceptional durability, outdoor weatherability and chemical resistance are required. Ideal for drum/chemical/industrial labeling, workplace hazard communications, logistics and healthcare labeling.	60"		5	I/P
Kimdura® Topcoated	Moisture resistant, biaxially oriented polypropylene. Compatible with a wide variety of thermal transfer ribbons.	52"	62#	4.2	F TT
0.5 mil, 1 mil and 2 mil Clear Laser Topcoated Polyester	Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing. Ideal for use with flexo, screen, letterpress and offset printing methods.	60"			F L UV TT

cont.

* BS5609 Section 3 Certified by EPSON C3500, C3400, C831, C7500 using EPSON DURABright® Ultra (Cyan, Magenta, Yellow, Black).

Key: F Flexo UV Ultra Violet TT Thermal Transfer DT Direct Transfer L Laser HP HP Indigo UV Inkjet I/P Inkjet (Dye) I/P Inkjet (Pigment)

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/ MIL	PRINT TECH.
VARIABLE PRINT FILM CONT.					
5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing.	54"		5.5	F L UV TT
7.5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing.	54"		7.5	F L UV TT
7 mil White Teslin®	An uncoated, porous, highly filled polyolefin film that is printable, durable, waterproof, secure, and adaptable. This sheet bonds readily and firmly with toners inks, adhesives, coatings and laminating films.	54"	77#	7	F UV TT
6 mil Polylioth®	White, opaque, two side matte finish. Excellent candidate for a wide range of applications where durability, strength, moisture, chemical resistance and superior printability are required. An excellent label and card stock. Outstanding combination of strength and rigidity.	51.5"	116#	6	F TT
10 mil Polylioth® * custom order	Two side, matte finish, white, opaque film. Excellent candidate for a wide range of applications where durability, strength, moisture, chemical resistance and superior printability are required. An excellent label and card stock, it has an outstanding combination of strength and rigidity.	51.5"	194#	10	F TT

OVERLAMINATES

0.5 mil Clear Non-topcoated Polyester	Optically clear. Excellent for use in applications requiring a durable overlaminate.	60"		.48	
1 mil Clear Non-topcoated Polyester	Optically clear. Smooth surface, high gloss and good dimensional stability. Excellent for use in applications requiring a durable overlaminate.	54"		1	
1 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film.	60"		1	F L
1 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		1	F L
2 mil Clear Non-topcoated Polyester	Strong. Good resistance to moisture, solvents, oils and high temperatures. Chemically primed for ink receptivity. Dimensionally stable, high strength and excellent chemical resistance.	60"		2	
2 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film with high resistance to scratching and abrasions.	60"		2	F L
2 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		2	F L

SPECIALTY FILM

1 mil Dry Erase Overlaminate	Topcoated clear overlaminate film designed for use with dry erase markers. Compatible with a variety of facestocks.	60"		1	
3.5 mil White Dry Erase Vinyl	Topcoated white film designed for use with dry erase markers.	54"		3.5	
Tyvek® 1073D	Spun-bonded polyolefin with very high internal strength and exceptional tear resistance.	54"	45.8#	7.5	F
5 mil Black Chalkboard Vinyl	Unique matte black vinyl designed to accept standard chalk. Good for use in classrooms, dorm rooms, home and office.	54"		5	F

PRIME PAPER

35# C1S Litho	Premium quality, mid gloss. Excellent conformability to small radius substrates. Most often used for pharmaceutical applications. Excellent strength to weight ratio. Crack resistant coating.	60"	35#	2.5	F UV
54# Semi Gloss	Super bright, two-side printable. Excellent solution for use across multiple printing platforms. Ideal for instant redeemable coupon applications.	60"	54#	2.4	F UV
60# Semi Gloss	Super bright, two-side printable. Excellent solution for use across multiple printing platforms. Ideal for instant redeemable coupon applications.	60"	60#	2.8	F UV

cont.

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/MIL	PRINT TECH.
PRIME PAPER CONT.					
60# Matte Litho	A premium quality C1S matte litho providing excellent printing and processing characteristics. Ion deposition printable.	60"	60#	3.2	F UV TT
54# Acu Gloss	One side clay coated. Excellent print results with flexo, letterpress and offset. Good conformability for small radii substrates.	60"	54#	2.5	F UV
55# Smudge Latex	Bright white, latex saturated litho. Manufactured for good conformability with moderate moisture and smudge resistance.	60"	56#	3.8	F L
57# High Gloss	High bright, cast coated. High internal strength, excellent ink receptivity and converting properties.	60"	57#	3.7	F UV
50# Uncoated Litho	High quality, smudge resistant. High-speed converting properties. Highly receptive to inks and markings of commonly used data systems.	60"	50#	3.5	F UV
60# Uncoated Litho	An economical uncoated stock compatible with most impact printing devices.	60"	60#	4.5	F UV

VARIABLE PRINT PAPER

Universal Thermal Transfer	Matte coated grade for use in thermal transfer printing. Excellent flexographic printing properties, no mottle, high brightness, and improved coating for extended die life. Wax-based ribbons are recommended with proper testing.	60"	38#	2.8	F TT
Direct Thermal HS	A bright white grade formulated for sharp imaging on a wide variety of direct thermal printers. Topcoated for resistance to blood, oil, fats and moisture. Good light stability for resistance to fading and background discoloration from UV light exposure. Suitable for flexographic pre-printing.	60"	46.5#	3.1	F UV DT
50# EDP	High quality and smudge-resistant. High-speed converting properties. Extremely receptive to inks and markings of commonly used data systems.	60"	50#	3.5	F
60# EDP	High quality and smudge-resistant. High-speed converting properties. Extremely receptive to inks and markings of commonly used data systems.	60"	60#	4.5	F
Economy Laser	Conformable, low-memory face. Good image contrast with low substrate show through. Suitable for a wide range of laser print systems.	60"	50#	3.5	F L
VIP Premium	A super smooth, high-bright laser and inkjet compatible stock.	54"	50#	3.8	F L

BOARDSTOCK

6pt C2S	Two side superior printability and appearance for a wide variety of print systems.	60"	106#	6	F UV
8pt C1S High Bright	Blue-white boardstock. Superior printability and appearance for a wide variety of print systems.	60"	108#	8	F UV
8pt Recycled C1S	10% post consumer waste recycled content.	60"	103#	8	F UV
8pt Uncoated	Good printability and appearance for a wide variety of print systems.	60"	103#	8	F UV
10pt C1S	Superior printability and appearance for a wide variety of print systems.	52"	118#	10	F UV
12pt C1S	Superior printability and appearance for a wide variety of print systems.	52"	133#	12	F UV
12pt Uncoated	Good printability and appearance for a wide variety of print systems.	52"	133#	12	F UV
14pt C1S	Superior printability and appearance for a wide variety of print systems.	52"	160#	14	F UV

FLUORESCENT

60# Red	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Orange	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/MIL	PRINT TECH.
FLUORESCENT CONT.					
60# Chartreuse	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	60"	59#	4.3	F
60# Green	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	54"	59#	4.3	F
60# Pink	Brightly colored and matte finished litho. Suitable for high visibility labeling. Excellent ink absorbency and processing characteristics.	54"	59#	4.3	F

FOILS & METALLIZED PAPER

Bright Silver	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Dull Silver	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Bright Gold	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Dull Gold	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	F UV
Silver Metallized Paper	Highly reflective. Offers conformability, strength and ink receptivity.	60"	51#	2.7	F UV

SPECIALTY PAPER

2 mil Clear Acetate	Cellulose based. Exhibits rigidity, dimensional stability and good ink receptivity. Excellent converting properties. Not recommended for outdoor use.	52"		2	F
54# Wet Strength High Gloss	Designed for applications where moisture or condensation is typically present. Excellent print surface and good converting properties.	60"	54#	2.5	F
Black Imaging Paper	Carbonless, self-contained pressure, black imaging facestock. Extremely sensitive. Can be silicone coated for use in multiply constructions or as a liner.	60"	22.5#	3.9	F

MAIL TABS

2 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54"	32.9#	2	F
2.5 mil Clear Polystyrene	Moisture resistant. Excellent resistance to fats, oils and greases. Not resistant to solvents or strong acids. Print treated for ink adhesion. Not recommended for outdoor use. Commonly used for mail tab, coupon and prime labeling applications.	54"	41#	2.5	F
Translucent MC Ultra	Exceptionally clear, translucent paper for mail tab applications where the highest level of view-through to the printed piece is required. Excellent converting and winding characteristics. An alternative to clear polystyrene mail tabs.	52" 60"	43#	2.1	F
Translucent MC	Moderate translucent paper. Should be considered for mail tab applications where modest view-through to the printed piece is required. Excellent converting and winding characteristics.	60"	40#	2.7	F
RC Mail Tab	Reverse coated paper used for mail tab closures.	60"	40#	2.6	F

COUPON

Diamond-Cote® EZ	Designed to be laminated with 50# to 60# basis weight facestocks to create one or two-side printed instant redeemable coupons. Universal release from any edge.	60"		1.5	F UV
Diamond-Cote® Tight	Designed to be laminated with heavy-weight facestocks to create two-side printed temporary ID cards. The universal pattern allows any die cut shape to be lifted and released cleanly without residue. <i>Coming soon - product improvements underway</i>	60"		1.5	F UV
2-Up LiftCote® 7.5"	Designed to be laminated with heavy-weight facestocks to create temporary ID cards.	60"		1.5	F UV
3-Up LiftCote® 11.25"	Designed to be laminated with heavy-weight facestocks to create temporary ID cards.	60"		1.5	F UV

cont.

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/MIL	PRINT TECH.
COUPON CONT.					
4-Up Lift Cote® 15"	Designed to be laminated with heavy-weight facestocks to create temporary ID cards.	60"		1.5	F UV
LiftCote® Longfeed	Designed to be manufactured in "portrait" orientation and to be laminated with heavy-weight facestocks to create temporary ID or retail buyers cards.	60"		1.5	F UV
Universal LiftCote®	Designed for integrated forms card applications that do not require lift lanes. The peeled layer has a 2 mil clear reinforcement film for the card and a 1.5 mil clear film base left on the form.	60"		3.5	F UV
LiftCote® Advantage	Designed to be laminated with heavy-weight facestocks to create temporary ID cards. In combination with 5 mil White Laser Polyester, it offers significant savings over other membership cards that utilize thicker gauge, laser printable films.	40"		1.5	F UV
60# Semi Gloss Diamond-Cote® SP	60# semi gloss uniquely laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	60"	94#	4	F UV
Red Fluorescent Diamond-Cote® SP	60# red fluorescent uniquely laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	60"	153#	9.4	F
Thermal Transfer Diamond-Cote® SP	Thermal transfer uniquely laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	60"	136#	8	F TT
Direct Thermal HS Diamond-Cote® SP	Bright white direct thermal uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	137#	8.6	F UV DT
2.6 mil Vision Gloss Diamond-Cote® SP	2.6 mil Vision Gloss uniquely laminated to a thin, clear BOPP creating a single-ply instant redeemable coupon.	54"	123#	8	F UV TT
HP IRComplete®	A single-ply, instant redeemable coupon utilizing a 2 mil clear topcoated polypropelene laminated to a thin, clear polypropelene. This solution permits single or double side printing.	60"		2.5	F
5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Provides superior toner and ink adhesion for laser and thermal transfer printing. Ideal for use with flexo, screen, letterpress, and offset printing methods.	54"		5	F UV L
7.5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing. Ideal for use with flexo, screen, letterpress, and offset printing methods.	54"		7.5	F UV L
8pt Dry Tag	NPS tag utilizing a 3.2 base and dry adhesive technology designed for single-side messaging. Tag stock is peeled from the base carrier without leaving tacky adhesive on the facestock or the liner.	60"	205#	14	F
10pt Dry Tag	NPS tag utilizing a 3.2 base and dry adhesive technology designed for single-side messaging. Tag stock is peeled from the base carrier without leaving tacky adhesive on the facestock or the liner.	52"	222#	16	F
12pt Dry Tag	NPS tag utilizing a 3.2 base and dry adhesive technology designed for single-side messaging. Tag stock is peeled from the base carrier without leaving tacky adhesive on the facestock or the liner.	52"	238#	18	F

* LiftCote® products have a narrow, ungummed patterned edge that allows for easy lifting and removal. They are designed for high-speed automatic applications. Flexographic inks reverse coated on the film layer produce two-side printed cards.

TAMPER EVIDENT

2.5 mil Silver Scratch Off Polystyrene	Utilizes a black base coating for opacity, silver coating top layer and a gloss top coating. Coatings can be scratched off to reveal a hidden message underneath.	54"	45#	2.5	NA
55# Tamper Evident Litho	Uncoated, white, highly destructible paper.	54"	55#	3.1	F
2 mil Silver Void Polyester	Selective release film with an imprinted silver "void" pattern to show undeniable evidence of tampering. Versatile topcoat suitable for solvent and water-based flexo, solvent based gravure as well as screen inks and selected UV inks. Topcoat is thermal transfer compatible.	54"		2	F UV TT
2 mil White Void Polyester	Selective release film with an imprinted white "void" pattern to show undeniable evidence of tampering. Versatile topcoat suitable for solvent and water-based flexo, solvent based gravure as well as screen inks and selected UV inks. Topcoat is thermal transfer compatible.	54"		2	F UV TT
2 mil Clear Void Polyester	Selective release film incorporating a "void" pattern to show undeniable evidence of tampering.	54"		2	F TT

cont.

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/ MIL	PRINT TECH.
TAMPER EVIDENT CONT.					
2 mil Custom Color Void Polyester	Topcoated polyester that utilizes a tinted adhesive to customize the void message.	54"		2	F UV TT
2 mil Custom Color/ Message Void Polyester	Topcoated polyester that allows for custom shapes/text/color match.	54"		2	F UV TT
Syntherm® TE	Topcoated, high-density polyethylene designed to destruct when removed. Accepts wax, wax/resin and resin thermal transfer ribbons.	60"	41#	4.1	F TT

ENVIRONMENTAL FRIENDLY

8pt C1S Recycled	Smooth with 10% post consumer waste recycled content.	60"	103#	8	F
8pt Uncoated Recycled	Smooth with 10% post consumer waste recycled content. Good printability and appearance for a wide variety of print systems.	60"	103#	8	F
2 mil Clear Acetate	Matte cellulose based. Exhibits rigidity, dimensional stability and good ink receptivity. Excellent converting properties. Not recommended for outdoor use.	52"		2	F
2 mil Clear EarthFirst®	Compostable. Made from an annually renewable resource. Excellent slip characteristics, high natural dyne level and excellent scratch resistance.	54"	41#	2	F

INKJET - UV

Products are topcoated to enhance the print quality on UV Inkjet presses. Media should be validated by the specific print system.

2 mil Clear UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	54"	40#	2	UVI F
2 mil White UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	54"	42#	2	UVI F
2 mil Bright Silver UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	54"	43.5#	2	UVI F
2 mil Matte Silver UV GL Polyester	Topcoated to enhance print quality for uv inkjet presses.	54"	42#	2	UVI F
2.4 mil White UV GL Polypropylene	White biaxially oriented film. Backside coated for excellent adhesive anchorage.	60"	30.8#	2.4	UVI F
2.6 mil White UV GL Polypropylene	High opacity, biaxially oriented with high gloss and good stiffness for automatic label dispensing. Backside coated for excellent adhesive anchorage.	60"	30.2#	2.7	UVI F
3.5 mil White UV GL Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	81.6#	3.5	UVI F
60# UV Semi Gloss	Super bright-white appearance.	60"	60#	2.8	UVI F
57# UV High Gloss	Bright cast coated paper. High internal strength and converting properties.	60"	57.4#	3.7	UVI F
Silver Metallized UV GL Paper	Highly reflective silver metallized paper offering conformability, strength and ink receptivity.	60"	56#	2.6	UVI F
8pt C1S UV GL Board	10% post consumer waste recycled content.	60"	103#	8	UVI F
Bright Silver UV GL Foil	Acrylic, foil that are laminated to a bleached kraft base sheet.	60"	70#	3.6	UVI F
Bright Gold UV GL Foil	Acrylic, foil that are laminated to a bleached kraft base sheet.	60"	70#	3.6	UVI F
60# UV Semi Gloss Diamond-Cote SP®	A 60# Semi Gloss sheet uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	94#	4.9	UVI F
Silver UV GL Polyester Void	Selective release film with an imprinted silver "void" pattern to show undeniable evidence of tampering.	54"		2	UVI F
Clear UV GL Polyester Void	Selective release film incorporating a "void" pattern to show undeniable evidence of tampering.	54"		2	UVI F

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/MIL	PRINT TECH.
------	---------------------	-------	-----------	---------	-------------

INKJET - DYE

Waterjet® media should be validated by the specific print system.

2.4 mil Gloss White Waterjet® Polypropylene	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	28.8#	2.4	U/D
2.4 mil Matte White Waterjet® Polypropylene	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	28.8#	2.4	U/D
60# Waterjet® High Gloss	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	64#	4	U/D
60# Extra Bright Waterjet® Semi Gloss	Bright white in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	60#	4.3	U/D
60# Waterjet® Premium Matte	Bright in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	64#	5	U/D
60# Extra Bright Waterjet® Diamond-Cote SP®	A 60# Semi Gloss sheet uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	98#	6.4	U/D

INKJET - PIGMENT

Media should be validated by the specific print system.

2.4 mil Gloss White Waterjet® Polypropylene	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	28.8#	2.4	U/P
2.4 mil Matte White Waterjet® Polypropylene	Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	28.8#	2.4	U/P
60# Extra Bright Waterjet® Semi Gloss	Bright white in appearance. Provides fast drying, excellent image resolution and durability through a wide color gamut.	60"	60#	4.3	U/P
60# Waterjet® High Gloss	This product offers fast drying, excellent image resolution and durability through a wide color gamut.	60"	64#	4	U/P
60# Extra Bright Waterjet® Diamond-Cote SP®	A 60# Semi Gloss sheet uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	98#	6.4	U/P
Inkjet Kimdura® Ultra*	Matte white in appearance. Designed for applications where exceptional durability, outdoor weatherability and chemical resistance are required. Ideal for drum/chemical/industrial labeling, workplace hazard communications, logistics and healthcare labeling.	60"		5	U/P
DualTech® Kimdura®	Matte white in appearance. Designed for applications where exceptional durability, outdoor weatherability and chemical resistance are required. Ideal for drum/chemical/industrial labeling, workplace hazard communications, logistics and healthcare labeling.	60"		3.5	U/P L
Endura® Inkjet Durable Paper	Matte white latex saturated paper. Offers outstanding durability and conformability. This stock is abrasion/scratch resistant, smudge-free, handwriteable and resists chemicals/solvents. Ideal for: drum/chemical/industrial labeling, workplace hazard communications, logistics labeling, healthcare labeling, coupons/shelf marketing.	60"		5	U/P

HP INDIGO

Products are topcoated to enhance the print quality on HP presses.

2 mil Clear HP TC Polypropylene	Clear biaxially oriented film. Excellent clarity for "no label" look. Good for automatic and hand applied label dispensing. Hot stamp compatible.	53"	31.6#	2	HP F
2.4 mil Gloss White HP TC Polypropylene	White biaxially oriented film. Backside coated for excellent adhesive anchorage.	54"	31.8#	2.4	HP F
2.6 mil Gloss White HP TC Polypropylene	High opacity, biaxially oriented film. Good stiffness for automatic label dispensing. Backside coated for excellent adhesive anchorage.	60"	30.2#	2.7	HP F
3.2 mil Clear HP TC Vinyl	Clear polymeric vinyl exhibiting excellent resistance to oils, chemicals, and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	74#	3	HP F
3.5 mil White HP TC Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	52#	3.5	HP F

* BS5609 Section 3 Certified by EPSON C3500, C3400, C831, C7500 using EPSON DURABright® Ultra (Cyan, Magenta, Yellow, Black).

cont.

FACE	PRODUCT DESCRIPTION	WIDTH	BASIS WT.	CAL/ MIL	PRINT TECH.
HP INDIGO CONT.					
<i>Products are topcoated to enhance the print quality on HP presses.</i>					
60# HP TC Semi Gloss	Super bright-white appearance suitable for roll-label and sheet-fed applications.	52"	60#	2.8	HP F
57# HP TC High Gloss	Bright cast coated gloss paper. High internal strength and converting properties.	52"	57.4#	3.7	HP F
Bright Silver HP Metallized Paper	Highly reflective. Offers conformability, strength and ink receptivity.	60"	51#	2.7	HP F
Bright Silver HP Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	HP F
Bright Gold HP Foil	Acrylic, topcoated foil that is laminated to a bleached kraft base sheet.	60"	70#	3.6	HP F
60# HP Semi Gloss Diamond-Cote® SP	A 60# Semi Gloss sheet uniquely laminated to a thin, clear BOPP creating a single-ply, instant redeemable coupon.	60"	94#	4.9	HP F
HP IRComplete®	A single-ply, instant redeemable coupon utilizing a 2 mil clear topcoated polypropylene laminated to a thin, clear polypropylene. This solution permits single or double side printing.	60"		2.5	HP F

LASER *Products are topcoated to enhance the print quality on laser presses.*

3.5 mil White Laser Topcoated Vinyl	Tough, durable polymeric film exhibiting excellent resistance to oils, chemicals and some solvents. Abrasion resistant. Good choice for outdoor labeling.	54"	52#	3.5	L
2 mil White Polyester CIRC	Proprietary computer imprintable matte topcoated film.	54"	42#	2	F UV TT
DualTech® Kimdura®	Matte white in appearance. Designed for applications where exceptional durability, outdoor weatherability and chemical resistance are required. Ideal for drum/chemical/industrial labeling, workplace hazard communications and healthcare labeling. BS5609 SECTION 2 CERTIFIED	60"		3.5	L U/P
5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing.	54"		5.5	F L UV TT
7.5 mil Matte White Laser Polyester	Rigid, coated two sides for adhesive anchorage. Excellent ink adhesion with UV cured and flexographic water-based systems. Provides superior toner and ink adhesion for laser and thermal transfer printing.	54"		7.5	F L UV TT
55# Smudge Latex	Bright white, latex saturated litho. Manufactured for good conformability with moderate moisture and smudge resistance.	60"	56#	3.8	F L
Economy Laser	Conformable, low-memory face. Good image contrast with low substrate show through. Suitable for a wide range of laser print systems.	60"	50#	3.5	F L
VIP Premium	A super smooth, high-bright white laser and inkjet compatible stock.	54"	50#	3.8	F L
60# Laser Semi Gloss	Versatile, laser printable stock.	60"	60#	2.8	F L
1 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film.	60"		1	F L
1 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		1	F L
2 mil Gloss Clear Laser TC Polyester	High gloss laser imprintable topcoated film with high resistance to scratching and abrasions.	60"		2	F L
2 mil Matte Clear Laser TC Polyester	Matte clear laser imprintable topcoated film.	60"		2	F L

Terms & Conditions:

Pre-testing is recommended using the printer(s) and ink system(s) to ensure compatibility. EarthFirst®, Kimdura®, Opticite®, Polyolith®, Syntherm®, Tyveck® and Valéron® are trademarks of the respected suppliers. Freight costs are set at a flat per msi rate. Acucote reserves the right to change, modify, or delete any product or program listing without notification. For more information, contact your Sales Representative or our Customer Service Team at 800.228.2683 or visit our website www.acucote.com.