

## **Liner Selection Guide**

Liner	Product Description	Caliper	Release Levels	Widths	
POLYESTER					
.92 mil	Clear, excellent dimensional stability and smoothness.	.92 mil	EZ, N, T	54.75", 60.75"	
1.2 mil	Clear, excellent dimensional stability and smoothness.	1.2 mil	EZ, N, T	54.75", 60.75"	
1.5 mil	Clear, excellent dimensional stability and smoothness.	1.42 mil	EZ, N, T	54.75", 60.75"	

44# F	Natural kraft, coated one side with glossy polypropylene.	3.1 mil	N, T	54.75" [N only], 60.75" [N, T only]
92#	Coated, two side high-density polykraft. Semi bleached base.	7.1 mil	N, N+, T, T+, XXT	54.75", 60.75"

## **PAPER**

30# P	White, softcalendered. Rough backside, basic text printable.	2.15 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	60.75"
40# P	Semi bleached, supercalendered, white kraft.	2.4 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	52.75", 54.75", 60.75"
40# Natural P	Natural, densified kraft.	2.6 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	54.75"
43# Glassine P	White glassine.	2.45 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	60.75"
50# P	Semi bleached, supercalendered, white kraft.	3.1 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	52.75", 54.75", 60.75"
3.2 Layflat P	White, softcalendered. Rough backside, basic text printable.	3.2 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	52.75", 54.75", 60.75"
60# P	Supercalendered, clay coated one side. Silicone coated on clay coated side.	3.8 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	54.75"
78# <sup>P</sup>	Supercalendered, clay coated one side. Silicone coated on clay coated side.	4.9 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	44.5", 50.5", 52.75", 54.75", 60.75"
83# <sup>P</sup>	Two side, clay coated sheet.	5.4 mil	EZ, EZ+, N, N+, T, T+, XT, XXT	54.75"

## **SPECIALTY**

Black Impact Image	Coated liner images upon impact.	3.9 mil	Various	60.75"
60# Semi Gloss	Color process printable.	2.8 mil	Various	60.75"
8pt Tag P	Color process printable.	8 mil	Various	60.75"
Laser Printable	Laser print receptive.	3.8 mil	Various	54.75"

P Printed liner available. Contact your local sales representative for details.

For more information, contact your Sales Representative or our Customer Service Team at 800.228.2683 or visit our website www.acucote.com.